MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC. 430 S. WHEELING RD. WHEELING, IL 60090

PRODUCT NAME: SLIDE ELECTRONIC RELEASE 42712N

EMERGENCY TELEPHONE: 800-535-5053 INFORMATION TELEPHONE: 847-541-7220 D.U.N.S. NUMBER: 00-299-4168

PREPARED BY: JIM ARMSTRONG

REVISION DATE: SEPT. 1, 2012 PRODUCT NUMBER: 42712N FAX NUMBER: 847-541-7986

SECTION I. IDENTIFICATION

CHEMICAL NAME: ORGANIC DEFOAMER SOLUTION CHEMICAL FAMILY: NON-IONIC SURFACTANT

FORMULA: 53135
SYNONYMS: SLIDE ELECTRONIC MOLD RELEASE
DOT HAZARD CLASSIFICATION: ORM-D
DOT SHIPPING NAME: CONSUMER COMMODITY
CHEMICAL ABSTRACT REGISTRY NUMBER: N/A, MIXTURE

IDENTIFICATION NUMBER: NONE H.M.I.S. RATING: 1,3,0,B

SECTION II. PHYSICAL DATA

BOILING POINT: N/A
FREEZING POINT: <-50' F.
SPECIFIC GRAVITY (H20 = 1): .81
WEIGHT PER GALLON @ 60 F.: 6.79
VAPOR PRESSURE @ 70 F. (MM HG): N/A
VAPOR DENSITY (AIR = 1): N/A
SOLUBILITY IN WATER, % BY WT.: PARTIALLY SOLUBLE
PERCENT VOLATILE BY WEIGHT: 96
EVAPORATION RATE (MINUTES): EXTREMELY RAPID
APPEARANCE AND ODOR: CLEAR OILY COLORLESS LICE

APPEARANCE AND ODOR: CLEÁR, OILY, COLORLESS LIQUID, SLIGHT ETHEREAL ODOR

SECTION III. HAZARDOUS INGREDIENTS

APPROX. WEIGHT %: CAS NUMBER: PEL(OSHA): ORGANIC DEFOAMER NON-IONIC *PROP. MIXTURE 1-6 N/A DIMETHYL ETHER 55-65 115-10-6 1000 1.2 DIFLUOROETHANE 30-40 75-37-6 1000

*) PRODUCT OF PPG INDUSTRIES - IDENTITY NOT DISCLOSED ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA DIRECTORY

SECTION IV. FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS IN AIR:

LEL: C.A. 5.8 UEL: N/A (VOLUME %)

FLAMMABLE LIMITS IN AIR: LEL: C.A. 3.8 UEL: N/A (VOLUME %)
FLASH POINT: N/A
AEROSOL FLAME PROJECTION TEST: 18" FLAME PROJECTION AS DETERMINED BY THE AEROSOL
FLAME PROJECTION TEST.
EXTINGUISHING MEDIA: DRY CHEMICAL, CO2, FOAM
SPECIAL FIRE FIGHTING PROCEDURES: SELF CONTAINED BREATHING APPARATUS
UNUSUAL FIRE & EXPLOSION HAZARDS: AEROSOLS MAY RUPTURE VIOLENTLY AT
TEMPERATURES. TEMPERATURES ABOVE 120 DEGREES F.

SECTION V. REACTIVITY DATA

STABILITY: STABLE INCOMPATIBILITY (MATERIALS TO AVOID): POWDERED OR ALKALINE EARTH METALS HAZARDOUS COMBUSTION BY-PRODUCTS: HF AND OTHER FLUORINE COMPOUNDS HAZARDOUS POLYMERIZATION: WILL NOT OCCUR CONDITIONS TO AVOID: OPEN FLAMES AND HIGH TEMPERATURES

SECTION VI. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 1,000 PPM

* EFFECTS OF OVEREXPOSURE *

INGESTION (SWALLOWING): N/A

INHALATION: EXCESSIVE INHALATION CAN PRODUCE DIZZINESS, NAUSEA, and HEADACHE. SKIN CONTACT: CONCENTRATED SPRAY MAY CAUSE FREEZING OF SKIN AREA EYE CONTACT: TEMPORARY IRRITATION

* EMERGENCY AND FIRST AID PROCEDURES *

SKIN: WASH WITH SOAP AND WATER INHALATION: REMOVE TO FRESH AIR LOCATION EYES: FLUSH WITH PLENTY OF WATER, CALL PHYSICIAN

SECTION VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: REMOVE LEAKING CONTAINER TO OUTSIDE DISPOSAL SITE.

WASTE DISPOSAL METHOD: EMPTY FULLY, INCLUDING GAS PRESSURE. DO NOT PUNCTURE OR INCINERATE. CAN BE RECYCLED OR ALTERNATIVELY REMOVED TO A SANITARY LANDFILL IN MOST LOCALITIES. CHECK APPLICABLE REGULATIONS.

SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT NEEDED WITH ADEQUATE VENTILATION VENTILATION: ADEQUATE VENTILATION NEEDED PROTECTIVE GLOVES: RECOMMENDED BUT NOT REQUIRED EYE PROTECTION: PROPER EYE CARE SHOULD BE PRACTICED IN ALL INDUSTRIAL OPERATIONS OTHER PROTECTIVE EQUIPMENT: AS YOUR COMPANY REQUIRES.

SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS AWAY FROM DIRECT SUNLIGHT, BELOW 120' F. DO NOT DROP, PUNCTURE, OR INCINERATE. OTHER PRECAUTIONS: DO NOT SPRAY DIRECTLY INTO FLAME. DO NOT SMOKE WHILE USING PRODUCT. DO NOT SPRAY ON FLOORS

SECTION X. CARCINOGENIC HAZARD

NO COMPONENT IN THIS PRODUCT HAS BEEN LISTED AS A CARCINOGEN BY IARU, N.T.P., OSHA, OR ACGIH.

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE, AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS, HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.