MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC. 430 S. WHEELING ROAD WHEELING, IL 60090

PRODUCT NAME: SLIDE HEAVY DUTY PAINTABLE

EMERGENCY TELEPHONE: 800-535-5053 INFORMATION TELEPHONE: 847-541-7220 FAX NUMBER: 847-541-7986 PREPARED BY: JIM ARMSTRONG REVISION DATE: SEPT. 1, 2012 PRODUCT NUMBER: 54912 D.U.N.S. NUMBER: 00-299-4168

SECTION I. IDENTIFICATION

CHEMICAL NAME: POLYALKYLENE GLYCOL CHEMICAL FAMILY: GLYCOL FORMULA: 54912 SYNONYMS: SLIDE HD PAINTABLE DOT HAZARD CLASSIFICATION: ORM-D DOT SHIPPING NAME: CONSUMER COMMODITY CHEMICAL ABSTRACT REGISTRY NUMBER: N/A, MIXTURE IDENTIFICATION NUMBER: NONE H.M.I.S. RATING: 1,3,0,B

SECTION II. PHYSICAL DATA

BOILING POINT: N/A FREEZING POINT: <-50' F. SPECIFIC GRAVITY (H20 =1): .81 WEIGHT PER GALLON @ 60 F.:6.79 VAPOR PRESSURE @ 70 F. (MM HG): N/A VAPOR DENSITY (AIR = 1): >1 SOLUBILITY IN WATER, % BY WT.: NOT SOLUBLE PERCENT VOLATILE BY WEIGHT: 90 EVAPORATION RATE (MINUTES): APPEARANCE AND ODOR: CLEAR, OILY, COLORLESS LIQUID, NO ODOR

SECTION III. HAZARDOUS INGREDIENTS

MATERIAL:	APPROX. WEIGHT % :	CAS NUMBER:	PEL(OSHA)
POLYALKYLENE GLYCC	DL 7-12	9003-13-8	N/A
DIMETHYL ETHER	55-65	115-10-6	1000
1,1 DIFLUOROETHANE	30-40	75-37-6	1000

ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA DIRECTORY

SECTION IV. FIRE AND EXPLOSION HAZARD DATA					
FLAMMABLE LIMITS IN AIR:	LEL:	UEL:	(VOLUME %)		
FLASH POINT: N/A					
AEROSOL FLAME PROJECTION TEST: 18" FLAME PROJECTION AS DETERMINED BY THE AEROSOL					
FLAME PROJECTION TEST.					
EXTINGUISHING MEDIA: DRY CHEMICAL, CO2, FOAM					
SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS					
UNUSUAL FIRE & EXPLOSION HAZARDS: AEROSOLS MAY RUPTURE VIOLENTLY AT TEMPERATURES					
ABOVE 120 DEGREES F.					

MATERIAL SAFETY DATA SHEET 54912

SLIDE PRODUCTS

PAGE 2

SECTION V. REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): POWDERED OR ALKALINE EARTH METALS HAZARDOUS COMBUSTION BY-PRODUCTS: HF AND OTHER FLUORINE COMPOUNDS HAZARDOUS POLYMERIZATION: WILL NOT OCCUR CONDITIONS TO AVOID: OPEN FLAMES AND HIGH TEMPERATURES

SECTION VI. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 1,000 PPM

***EFFECTS OF OVEREXPOSURE ***

INGESTION (SWALLOWING): N/A INHALATION: EXCESSIVE INHALATION CAN PRODUCE DIZZINESS, NAUSEA, AND HEADACHE SKIN CONTACT: CONCENTRATED SPRAY MAY CAUSE FREEZING OF SKIN AREA EYE CONTACT: TEMPROARY IRRITATION

* EMERGENCY AND FIRST AID PROCEDURES *

SKIN: WASH WITH SOAP AND WATER INHALATION: REMOVE TO FRESH AIR LOCATION EYES: FLUSH WITH PLENTY OF WATER, CALL PHYSICIAN IMMEDIATELY.

SECTION VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASE D OR SPILLED: REMOVE LEAKING CONTAINER TO OUTSIDE DISPOSAL SITE.

WASTE DISPOSAL METHOD: EMPTY FULLY, INCLUDING GAS PRESSURE. DO NOT PUNCTURE OR INCINERATE. CAN MAY BE RECYCLED OR ALTERNATIVELY REMOVED TO A SANITARY LANDFILL IN MOST LOCALITIES. CHECK APPLICABLE REGULATIONS.

SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT NEEDED WITH ADEQUATE VENTILATION VENTILATION: ADEQUATE VENTILATION NEEDED PROTECTIVE GLOVES: RECOMMENDED BUT NOT REQUIRED EYE PROTECTION: PROPER EYE CARE SHOULD BE PRACTICED IN ALL INDUSTRIAL OPERATIONS. OTHER PROTECTIVE EQUIPMENT: AS YOUR COMPANY REQUIRES.

SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS AWAY FROM DIRECT SUNLIGHT, BELOW 120'F . DO NOT DROP, PUNCTURE, OR INCINERATE. OTHER PRECAUTIONS: DO NOT SPRAY DIRECTLY INTO FLAME. DO NOT SMOKE WHILE USING PRODUCT. DO NOT SPRAY ON FLOORS.

SECTION X. CARCINOGENIC HAZARD

NO COMPONENT IN THIS PRODUCT HAS BEEN LISTED AS A CARCINOGEN BY IARU, N.T.P., OSHA, OR ACGIH.

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIEN AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE, AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS, HAVE CONSULTED IN PREPARING THIS M.S.D.S.

http://www.slideproducts.com/mold.htm