

## MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC.  
430 S. WHEELING ROAD  
WHEELING, IL 60090

PRODUCT NAME: SLIDE PAINTABLE BIODEGRADABLE MR 40035N

EMERGENCY TELEPHONE: 800-535-5053  
INFORMATION TELEPHONE: 847-541-7220  
FAX NUMBER: 847-541-7986  
PREPARED BY: JIM ARMSTRONG

REVISION DATE: SEPT. 1, 2012  
PRODUCT NUMBER: 40035N  
D.U.N.S. NUMBER: 00-299-4168

### SECTION I. IDENTIFICATION

CHEMICAL NAME: METHYL BUTYL, METHYL ISOPROPYL BENZYL SOLUTION  
CHEMICAL FAMILY: SILICONE  
FORMULA: 53126  
SYNONYMS: SLIDE PAINTABLE  
DOT HAZARD CLASSIFICATION: 2.1  
DOT SHIPPING NAME: COMPRESSED GAS NOS (DIMETHYL ETHER, 1,1-DIFLUOROETHANE)  
CHEMICAL ABSTRACT REGISTRY NUMBER: N/A, MIXTURE  
IDENTIFICATION NUMBER: UN# 1954  
REQUIRED SHIPPING LABELS: FLAMMABLE GAS  
PACKING GROUP: NONE  
H.M.I.S. RATING: 1,3,O,B

### SECTION II. PHYSICAL DATA

DATA IN SECTION II APPLY TO CONCENTRATE BEFORE ADDING PROPELLANT  
BOILING POINT: N/A  
FREEZING POINT: <-50° F.  
SPECIFIC GRAVITY (H<sub>2</sub>O =1): .81  
WEIGHT PER GALLON @ 60 F.:6.79  
VAPOR PRESSURE @ 70 F. (MM HG): N/A  
VAPOR DENSITY (AIR = 1): >1  
SOLUBILITY IN WATER, % BY WT.: PARTIALLY SOLUBLE  
PERCENT VOLATILE BY WEIGHT: 97  
EVAPORATION RATE (MINUTES):  
APPEARANCE AND ODOR: CLEAR, OILY, COLORLESS LIQUID, SLIGHT ETHEREAL ODOR

### SECTION III. HAZARDOUS INGREDIENTS

MATERIAL:	APPROX. WEIGHT % :	CAS NUMBER:	PEL(OSHA)
PAINTABLE SILICONE FLUID	1-5	68037-74-4	N/A
DIMETHYL ETHER	55-65	115-10-6	1000
1,1 DIFLUOROETHANE	30-40	75-37-6	1000

ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA DIRECTORY  
\*\*CONTAINS NO OZONE DEPLETING CHEMICALS\*\*

### SECTION IV. FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS IN AIR: LEL: UEL: (VOLUME %)  
FLASH POINT: N/A  
AEROSOL FLAME PROJECTION TEST: 18" FLAME PROJECTION AS DETERMINED BY THE AEROSOL FLAME PROJECTION TEST.  
EXTINGUISHING MEDIA: DRY CHEMICAL, CO<sub>2</sub>, FOAM  
SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS  
UNUSUAL FIRE & EXPLOSION HAZARDS: AEROSOLS MAY RUPTURE VIOLENTLY AT TEMPERATURES ABOVE 120 DEGREES F.

---

#### SECTION V. REACTIVITY DATA

---

STABILITY: STABLE  
INCOMPATIBILITY (MATERIALS TO AVOID): POWDERED OR ALKALINE EARTH METALS  
HAZARDOUS COMBUSTION BY-PRODUCTS: HF AND OTHER FLUORINE COMPOUNDS  
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR  
CONDITIONS TO AVOID: OPEN FLAMES AND HIGH TEMPERATURES

---

#### SECTION VI. HEALTH HAZARD DATA

---

THRESHOLD LIMIT VALUE: 1,000 PPM

#### \*EFFECTS OF OVEREXPOSURE \*

INGESTION (SWALLOWING): N/A  
INHALATION: EXCESSIVE INHALATION CAN PRODUCE DIZZINESS, NAUSEA, AND HEADACHE  
SKIN CONTACT: CONCENTRATED SPRAY MAY CAUSE FREEZING OF SKIN AREA  
EYE CONTACT: TEMPORARY IRRITATION

#### • EMERGENCY AND FIRST AID PROCEDURES \*

SKIN: WASH WITH SOAP AND WATER  
INHALATION: REMOVE TO FRESH AIR LOCATION  
EYES: FLUSH WITH PLENTY OF WATER, CALL PHYSICIAN IMMEDIATELY.

---

#### SECTION VII. SPILL OR LEAK PROCEDURES

---

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: REMOVE LEAKING CONTAINER TO OUTSIDE DISPOSAL SITE.  
WASTE DISPOSAL METHOD: EMPTY FULLY, INCLUDING GAS PRESSURE. DO NOT PUNCTURE OR INCINERATE. CAN MAY BE RECYCLED OR ALTERNATIVELY REMOVED TO A SANITARY LANDFILL IN MOST LOCALITIES. CHECK APPLICABLE REGULATIONS.

---

#### SECTION VIII. SPECIAL PROTECTION INFORMATION

---

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT NEEDED WITH ADEQUATE VENTILATION  
VENTILATION: ADEQUATE VENTILATION NEEDED  
PROTECTIVE GLOVES: RECOMMENDED BUT NOT REQUIRED  
EYE PROTECTION: PROPER EYE CARE SHOULD BE PRACTICED IN ALL INDUSTRIAL OPERATIONS.  
OTHER PROTECTIVE EQUIPMENT: AS YOUR COMPANY REQUIRES.

---

#### SECTION IX. SPECIAL PRECAUTIONS

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS AWAY FROM DIRECT SUNLIGHT, BELOW 120°F. DO NOT DROP, PUNCTURE, OR INCINERATE. OTHER PRECAUTIONS: DO NOT SPRAY DIRECTLY INTO FLAME. DO NOT SMOKE WHILE USING PRODUCT. DO NOT SPRAY ON FLOORS.

---

#### SECTION X. CARCINOGENIC HAZARD

---

NO COMPONENT IN THIS PRODUCT HAS BEEN LISTED AS A CARCINOGEN BY IARC, N.T.P., OSHA, OR ACGIH.

---

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE, AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS, HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.

<http://www.slideproducts.com/mold.htm>