

MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC.
430 S. WHEELING ROAD
WHEELING, IL 60090

PRODUCT NAME: SLIDE RESIN REMOVER AEROSOL

EMERGENCY TELEPHONE: 800-535-5053
INFORMATION TELEPHONE: 847-541-7220
FAX NUMBER: 847-541-7986
PREPARED BY: JIM ARMSTRONG

REVISION DATE: SEPT. 1, 2012
PRODUCT NUMBER: 41914
D.U.N.S. NUMBER: 00-299-4168

SECTION I. IDENTIFICATION

CHEMICAL NAME: CYCLIC AMIDE AND LACTONE BLEND
CHEMICAL FAMILY: LACTONE
FORMULA: 41914
SYNONYMS: "THE STRIPPER"
DOT HAZARD CLASSIFICATION: ORM-D
DOT SHIPPING NAME: CONSUMER COMMODITY
CHEMICAL ABSTRACT REGISTRY NUMBER: N/A, MIXTURE
IDENTIFICATION NUMBER: NONE
H.M.I.S. RATING: 2,3,0,B

SECTION II. PHYSICAL DATA

BOILING POINT: 103-399 DEGREES F.
FREEZING POINT: <-45 DEGREES F.
SPECIFIC GRAVITY: (H2O =1): 1.15
WEIGHT PER GALLON @ 60 F.: 9.16
VAPOR PRESSURE OF CONCENTRATE @ 70 F. (MM HG): NIL
VAPOR DENSITY (AIR = 1): >1
SOLUBILITY IN WATER, % BY WT.: PARTIALLY WATER-MISCIBLE
PERCENT VOLATILE BY WEIGHT: 100
EVAPORATION RATE (MINUTES): SEVERAL HOURS, SLOW
APPEARANCE AND ODOR: PALE STRAW-COLORED LIQUID – FISHY ODOR

SECTION III. HAZARDOUS INGREDIENTS

MATERIAL:	APPROX. WT. %:	CAS NUMBER:	PEL(OSHA)
GAMMA-BUTYROLACTONE	35-40	96-48-0	NOT ESTABLISHED
N-METHYL-2-PYRROLIDONE	35-40	872-50-4	NOT ESTABLISHED
PROPANE A-108	1-10	74-98-6	1000 PPM
N-PROPYL BROMIDE	25-30	106-94-5	100 PPM*

CONTAINS NO OZONE DEPLETING CHEMICALS
ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA DIRECTORY
*OSHA PEL AND ACGIH TLV NOT ESTABLISHED. SOLVENT MANUFACTURER RECOMMENDS A
WORKPLACE EXPOSURE GUIDELINE OF 100 PPM 8 HOUR. TWA BASED ON THE SCIENTIFIC
ASSESSMENT OF SOLVENT MIXTURE AND OTHER EXISTING TOXICOLOGICAL DATA.

SECTION IV. FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS IN AIR: LEL: 1.00 UEL: 10.0 (VOLUME %)
FLASH POINT: N/A (AEROSOLS ARE NORMALLY TESTED WITH FLAME PROJECTION)
AEROSOL FLAME PROJECTION TEST: 18" EXTENSION AT 70' F
EXTINGUISHING MEDIA: DRY CHEMICAL, FOAM, CO2
SPECIAL FIRE FIGHTING PROCEDURES: CHLORINATED HYDROCARBON FORM HCl AND TRACES OF
PHOSGENE UPON PYROLYSIS
UNUSUAL FIRE & EXPLOSION HAZARDS: AEROSOLS MAY RUPTURE VIOLENTLY AT TEMPERATURES
OVER 120 DEGREES F.

SECTION V. REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): WATER, FREE-RADICAL GENERATORS

CONDITIONS TO AVOID: SEE SECTION IV – APPLICABLE TO AEROSOLS, NOT PRODUCT

HAZARDOUS COMBUSTION BY-PRODUCTS: SEE SECTION IV

CONDITIONS TO AVOID: TEMP. ABOVE 120' F. – DIRECT SUNLIGHT

SECTION VI. HEALTH HAZARD DATA

TLV: NOT ESTABLISHED FOR VERY HIGH-BOILING SOLVENTS (399' F.), BECAUSE ADEQUATE VAPOR LEVELS FOR ANIMAL INHALATION INHALATION STUDIES CANNOT BE OBTAINED AT ROOM TEMP.

ORAL TOXICITY: LD50(WHITE RATS) IS 1.55 CC/KG BODY WEIGHT

• EFFECTS OF OVEREXPOSURE *

INGESTION (SWALLOWING): N/A

INHALATION: IRRITATION OF TRACHEA AND LUNGS

SKIN CONTACT: DE-FATTING OF SKIN

EYE CONTACT: TEMPORARY IRRITATION

• EMERGENCY AND FIRST AID PROCEDURES *

SKIN: WASH WITH SOAP AND WATER, APPLY HAND CREAM

INHALATION: REMOVE TO FRESH AIR LOCATION SWAY FROM EXPOSURE SITE

EYES: RINSE WITH PLENTY COOL CLEAN WATER UNTIL IRRITATION SUBSIDES, CONSULT PHYSICIAN, APPLY ICE PACK.

SECTION VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: REMOVE LEAKING CONTAINER TO OUTSIDE DISPOSAL SITE.

WASTE DISPOSAL METHOD; EMPTY FULLY, INCLUDING GAS PRESSURE. DO NOT PUNCTURE OR INCINERATE. CAN MAY BE RECYCLED OR ALTERNATIVELY REMOVED TO A SANITARY LANDFILL – CHECK APPLICABLE REGULATIONS.

SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTON: (SPECIFY TYPE): NOT NEEDED WITH ADEQUATE VENTILATION

VENTILATION: ADEQUEATE VENTILATION RECOMMENDED

PROTECTIVE GLOVES: NEOPRENE GLOVES

EYE PROTECTON: PROPER EYE CARE IS NEEDED IN ALL INDUSTRIAL OPERATIONS

OTHER PROTECTIVE EQUIPMENT: AS REQUIRED BY YOUR COMPANY – SAFETY GLASSES WITH SIDE SHIELDS.

SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS AWAY FROM HEAT SOURCES OR DIRECT SUNLIGHT – DO NOT PUNCTUREOR INCINERATE – DO NOT DROP!!

OTHER PRECAUTIONS: DO NOT SPRAY NEAR FLAME OR OPEN LIGHTS. DO NOT SPRAY ON PAINTED SURFACES: PRODUCT WILL DAMAGE VARNISH AND ALKYD COATINGS.

AVOID OVER-SPRAYING ONTO FLOORS OR SLIPPERY SURFACE MAY RESULT.

SECTION X. EFFECTS OF PROLONGED EXPOSURE

NONE KNOWN

SECTION XI. CARCINOGENIC HAZARD

CALIFORNIA PROPOSITION 65: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM

SECTION XII. REPORTING REQUIREMENTS

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) REQUIRED TO BE REPORTED UNDER SARA TITLE III, SECTION 313: NONE
ALL COMPONENTS OF SLIDE RESIN REMOVER 41916T ARE LISTED ON THE TOXIC SUBSTANCES CONTROL ACT (TSCA) DIRECTORY.

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCTS SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS, HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.

<http://www.slideproducts.com/cleaners.htm>