MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC. 430 S. WHEELING ROAD WHEELING, IL 60090

PRODUCT NAME: SLIDE NO-RUST AEROSOL

EMERGENCY TELEPHONE #: 800-535-5053 INFORMATION TELEPHONE #: 847-541-7220 FAX NUMBER: 847-541-7986

PREPARED BY: JIM ARMSTRONG

REVISION DATE: SEPT. 1, 2012 PRODUCT NUMBER: 40212 D.U.N.S. NUMBER: 00-299-4168

SECTION I. IDENTIFICATION

CHEMICAL NAME: RUST PREVENTIVE COMPOUND CHEMICAL FAMILY: PETROLEUM DERIVATIVE

FORMULA: 53081 SYNONYMS: NO-RUST

DOT HAZARD CLASSIFICATION: ORM-D

DOT SHIPPING NAME: CONSUMER COMMODITY

CHEMICAL ABSTRACT REGISTRY NUMBER: N/A, MIXTURE

IDENTIFICATION NUMBER: NONE

H.M.I.S. RATING: 1, 3,O,B

SECTION II. PHYSICAL DATA

BOILING POINT: RANGE 300-350 DEGREES F.

FREEZING POINT: <-40 DEGREES F. SPECIFIC GRAVITY (H20=1): 0.83 WEIGHT PER GALLON @ 60 F.: 8.48

VAPOR PRESSURE OF CONCENTRATE @ 70F: 2

VAPOR DENSITY (AIR=1): >1

SOLUBILITY IN WATER, % BY WT.: NIL PERCENT VOLATILE BY WEIGHT: 94 EVAPORATION RATE (MINUTES): 25

APPEARANCE AND ODOR: BROWN LIQUID-HYDROCARBON SOLVENT ODOR

SECTION III. HAZARDOUS INGREDIENTS

MATERIAL:	APPROX. WEIGHT %:	CAS NUMBER:	PEL(OSHA)	
LECITHIN	1-5	68910-52-1*	N/A	
KEROSENE	60-70	8008-20-6	400	
NAPTHALENESULFONIC ACID,				
DINONYL-, CALCIM SA	ALT 4-10	57855-77-3	N/A	
PROPANE A-108	20-30	74-98-6	1000	
AND CONTRACTOR OF COME DEED DEED CONTRACTOR OF CONTRACTOR				

CONTAINS NO OZONE DEPLETING CHEMICALS

ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA DIRECTORY

NO COMPONENT OF THIS PRODUCT IS CONSIDERED A CARCINOGEN

SECTION IV. FIRE AND EXPLOSION DATA

FLAMMABLE LIMITS IN AIR: LEL: 1.0 UEL: 9.5 (% VOLUME IN AIR)

FLASH POINT: N/A

AEROSOL FLAME PROJECTION TEST: 18" EXTENSION AT 70' F.

EXTINGUISHING MEDIA: DRY CHEMICAL, FOAM, CO2

SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS

UNUSUAL FIRE & EXPLOSION HAZARDS: AEROSOLS MAY RUPTURE VIOLENTLY AT TEMPERATURES

ABOVE 120 DEGREES F.

SECTION V. REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): NONE KNOWN HAZARDOUS COMBUSTION BY-PRODUCTS: SEE SECTION IV

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: TEMP. ABOVE 120' F.-DIRECT SUNLIGHT-DO NOT SPRAY NEAR FLAME OR

OPEN LIGHTS.

SECTION VI. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 130 PPM

EFFECTS OF OVEREXPOSURE

INGESTION (SWALLOWING): N/A

INHALATION: GIDDINESS, NAUSEA, POSSIBLE NARCOSIS

SKIN CONTACT: DEFATTING SKIN

EYE CONTACT: TEMPORARY IRRITATION

EMERGENCY AND FIRST AID PROCEDURES

SKIN: WASH WITH SOAP AND WATER. APPLY HAND CREAM

INHALATION: REMOVE TO FRESH-AIR LOCATION AWAY FROM EXPOSURE SITE

EYES: RINSE WITH PLENTY COOL CLEAN WATER UNTIL IRRITATION SUBSIDES, CONSULT

PHYSICIAN IMMEDIATELY.

SECTION VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: REMOVE LEAKING CONTAINER TO OUTSIDE DISPOSAL SITE.WSTE DISPOSAL METHOD: EMPTY FULLY, INCLUDING GAS PRESSURE. DO NOT PUNCTURE OR INCINERATE. CAN MAY BE RECYCLED OR ALTERNATIVELY REMOVED TO A SANITARY LANDFILL IN MOST LOCALITIES. CHECK APPLICABLE REGULATIONS.

SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT NEEDED WITH ADEQUATE VENTILATION

VENTILATION: ADEQUATE VENTILATION RECOMMENDED PROTECTIVE GLOVES: NOT REQUIRED BUT RECOMMENDED

EYE PROTECTION: PROPER EYE CARE IS NEEDED IN ALL INDUSTRIAL OPERATIONS

OTHER PROTECTIVE EQUIPMENT: AS REQUIRED BY YOUR COMPANY.

SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS AWAY FROM HEAT SOURCES OR DIRECT SUNLIGHT-DO NOT PUNCTURE OR INCINERATE-DO NOT DROP!! OTHER PRECAUTIONS: DO NOT SPRAY NEAR FLAME OR OPEN LIGHTS.

SECTION X. SARA TITLE III REPORTING

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS REQUIRED TO BE REPORTED UNDER SARA TITLE III, SECTION 313: NONE

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIES, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200. AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS, HAVE BEEN CONSIDERED IN PREPARING THIS M.S.D.S.

http://www.slideproducts.com/rust.htm