
MERCURY DISPLACEMENT INDUSTRIES, INC.

INDUSTRIAL & ELECTRIC SUPPLY CO.
Tel: 956-541-3743 Fax: 956-541-2106
Toll Free: 800-880-3743

360NO-120A-18



* CONTACT RESISTANCE .002 ohms
* DIELECTRIC WITHSTAND 2,500 VAC RMS
* OPERATE TIME 50 MILLISECONDS
* RELEASE TIME 80 MILLISECONDS
* RATINGS:
  CONTACTS: 60 AMPS @ 480 VAC RES
  48 AMPS @ 600 VAC RES
  COIL: 120V 50/60 Hz
  CURRENT: 144 mA
  RESISTANCE: 417 Ω
  VA: 17.4 WATTS: 8.7
* TEMPERATURE RANGE -35° TO +85° C
* COIL TERMINALS #6 BINDING HEAD SCREWS TORQUE TO 7-IN-LBS
* LOAD TERMINALS 2-8 A.W.G. COMPRESSION TYPE TORQUE TO 45 IN-LBS
* 3 POLE / SINGLE THROW
* MAGNETICALLY ACTIVATED

939S LISTED
LR 41198 CERTIFIED
INDUSTRIAL CONTROL EQUIPMENT

* LIFE CYCLE ENDURANCE TESTS: U.L. 508 @ 100,00 & CSA 22.2 @ 250,000 CYCLES

J.J.S. 05-21-08

Contactors - Relays - Switches

www.MroCrib.com